



VpCI® ADDITIVES FOR WATER TREATMENT



VpCI®-649 BD



PRODUCT DESCRIPTION

VpCI-649 BD is a unique concentrated liquid formulation that protects ferrous and non-ferrous metals from corrosive solutions. In addition, this product is designed to provide long-term protection in fresh water, steam, and glycol closed loop systems. VpCI-649 BD also includes preservatives against biogrowth.

VpCI-649 BD is effective as a replacement for nitrite/chromate-based formulations.

VpCI-649 BD combines contact and volatile corrosion inhibitors along with anti-scalants in a non-toxic formulation that does not contain nitrites, phosphates, chromates, or heavy metals. Being environmentally safe, this product helps solve the problem of disposal particularly for large quantities of water.

FEATURES

- Effective for a broad range of applications to stop aggressive corrosion in systems containing fresh water, glycol coolants, etc.
- Environmentally friendly and nitrite-free
- Low concentration effectiveness provides economical treatment
- Vapor phase action provides protection to areas that contact inhibitors cannot reach
- Contains an acrylic polymer to prevent scale formation
- Readily water-soluble liquid for easy application
- Multi-metal protection
- Effective in low dosages
- Does not contain free amines
- Contains molybdate tracer (for product without molybdate order VpCI-649 BD MF)

TYPICAL APPLICATIONS

- Inhibitor for closed loop cooling systems
- Fire extinguishing systems
- Inhibitor for hydrostatic testing of pipelines, casings, tanks, and valves
- Inhibitor for packer fluid applications
- Prevents water-bottom corrosion in oil storage tanks
- Alkanolamine sweeteners
- Pulp and paper process equipment
- Mines, mining, and earth moving equipment
- Inhibitor for lay-up application of cooling towers

DOSAGE

- For operational systems such as closed loop, start at 2,500-3,000 ppm (0.25-0.3%). Additional bio dispersant may need to be added depending on the system.
- For seasonal lay-up application, (up to 6 months) use VpCI-649 BD at a concentration of 0.5% of inhibitor by volume (wet lay-up method)
- Hydrotesting concentration varies from 0.5-2% by weight depending on application
- For systems already containing molybdate please use VpCI-649 BD MF which does not contain tracer


PACKAGING

VpCI-649 BD is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk. The products should be stored in tightly closed containers. Shelf life is 2 years.

TYPICAL PROPERTIES

VpCI-649 BD	
Appearance	Clear amber liquid
Density	9.3-9.8 lb/gal (1.12-1.18 kg/l)
Type	Water-based
Non-volatile Content	48-55%
pH	9.3-9.8 (Neat)





FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
 Revised 2/22/13, Cortec Corporation 2002-2013. All rights reserved. Supersedes: 3/17/11
 © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.
 ISO accreditation applies to Cortec's processes only.